






# FR 5400 | Teleskopvollauszug




## Spezifikationen

-  seitliche Schubkastenmontage
-  19,5 mm
-  dynamisch bis 250 kg
-  Chromstahlkugelläufig
-  Stahl, verzinkt

## Hinweise

- symmetrische Ausführung – daher beidseitig verwendbar
- unzerlegbar

## Einbauabmessungen



Länge	Auszugsweg	Gewicht	Best. Nr.
		pro Paar	verzinkt
mm	mm	kg	
203,2	203,2	1,95	*
254,0	254,0	2,45	*
304,8	304,8	2,98	*
355,6	355,6	3,48	▶ 5503
406,4	406,4	4,00	▶ 5504
457,2	457,2	4,70	▶ 5505
508,0	508,0	5,20	▶ 5506
558,8	558,8	5,55	▶ 5507
609,6	609,6	6,05	▶ 5508
660,4	660,4	6,60	▶ 5509
711,2	711,2	7,10	▶ 5510
762,0	762,0	7,55	▶ 5511
812,8	812,8	8,10	▶ 5512
863,3	863,3	8,60	▶ 5513
914,4	914,4	9,10	▶ 5514
965,2	965,2	9,60	▶ 5515
1.016,0	1.016,0	10,30	▶ 5516
1.066,8	1.066,8	11,00	▶ 5517
1.117,6	1.117,6	11,40	▶ 5518
1.168,4	1.168,4	11,80	▶ 5519
1.219,2	1.219,2	12,30	▶ 5520
1.270,0	1.270,0	12,70	▶ 5521
1.320,0	1.320,0	13,20	▶ 5522
1.371,6	1.371,6	13,60	▶ 5523
1.422,4	1.422,4	14,10	▶ 5524
1.473,2	1.473,2	14,60	▶ 5525
1.524,0	1.524,0	15,40	▶ 5526

Verpackungseinheit – Garnituren pro Karton: 203,2 bis 609,6 mm: 4 | 660,4 bis 863,3 mm: 2 | 914,4 bis 1.524,0 mm: 1 ▶ Lagerartikel | \* auf Anfrage